



FTT Mass Loss Calorimeter Spare Parts List

<i>Part Number</i>	<i>Part type</i>	<i>Part Name</i>	<i>Unit Price</i>	<i>Notes</i>	<i>Instrument</i>
FTT030	Burner	1 - 2 mm burner gravel (1 kg bag)	POA	Price per 1 kg	MLC
M073-4	Burner	Sand box calibration burner assembly	POA	Including gravel and ceramic fibre layers	MLC
HFM Recal	Calibration	Calibration of heat fluxmeter	POA	Original to be returned to FTT	MLC
C209-4	Ceramic	Load cell cover	POA	Rectangular cover with slot	MLC
U199-4	Ceramic	Shutter Pad - Set of 2 (L/H & R/H)	POA		MLC
FTT0156	Controller	Temperature controller for Cone Calorimeter	POA		MLC
FTT0154	Flow control	Flashback arrestor assembly	POA	With 8 mm hose nipple on each end	MLC
U186-4	Gauge	23 mm spacing gauge (cone to sample)	POA	Use for sample holder with edge frame	MLC
U187-4	Gauge	25 mm spacing gauge (cone to heat flux meter or sample)	POA	Use to position heat flux meter at correct height or sample with no edge frame	MLC
FTT0012	Heat Flux Meter	S/A Heat flux meter assembly	POA		MLC
U135	Heater	Heater element winding	POA		MLC
U149	Heater	Cone heater assembly and thermocouples	POA		MLC
U216	Heater	Cone winding termination kit (ring terminal, sleeve and Autostic)	POA	set of 2 (ring + pyrex sleeve + Autostic)	MLC
4473	Load cell	Load cell controller	POA		MLC
FTT0013	Sample	S/A Sample holder assembly (tray and edge frame)	POA		MLC
U197	Sample	Ceramic fibre backing pads (4 pieces)	POA	100 x 100 x 25 mm (4 per pack)	MLC
4084	Spark	New spark generator	POA	Continuous spark	MLC
4397	Spark	10 kV spark generator unit	POA	Intermittent spark, no detection	MLC
M015-4	Spark	2.5 mm electrode assembly with Tufnol block	POA		MLC
U215-4	Support	Dual height fluxmeter/burner holder	POA	Bracket for side of cone heater to allow heat flux meter to be positioned at 25 or 60 mm from the bottom of the heater	MLC
4615	Thermocouple	1.5 mm thermocouple olive and nut	POA		MLC
4822	Thermocouple	Thermocouple for stack	POA		MLC